

MATERIAL SAFETY DATA SHEET

EASTMAN CHEMICAL RESINS, INC.
Box 511
Kingsport, TN 37662
800-EASTMAN (BUSINESS)

For transportation emergency, call CHEMTREC at 800-424-9300 or 800-EASTMAN

1 PRODUCT IDENTIFICATION

PRODUCT NAME	PICCO® 6115 HYDROCARBON RESIN
CHEMICAL DESCRIPTION	aromatic hydrocarbon resin
CAS NUMBER	mixture

2 COMPOSITION / INFORMATION ON INGREDIENTS

This product is considered hazardous according to the OSHA Hazard Communication Standard 29CFR1910.1200 due to flammable dust potential.

If this product is used in a manner that could generate particulates (dust), refer to MSDS Section 7, Handling and Storage, and Section 8, Recommended Exposure Limits and Personal Protective Equipment.

3 HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

WARNING!

Static charges generated by emptying package in or near flammable vapors may cause flash fire.
May form flammable dust-air mixtures.
Surfaces subject to spills may become slippery.

POTENTIAL HEALTH EFFECTS

May cause eye irritation by mechanical abrasion.
May cause skin irritation by mechanical abrasion.
Inhalation may cause respiratory tract irritation.
Prolonged or repeated contact may cause skin irritation.

Refer to Section 5 for Hazardous Combustion Products, and Section 10 for Hazardous Decomposition/Hazardous Polymerization Products.

MARKETED BY
**HARWICK STANDARD
DISTRIBUTION CORPORATION**
60 S. Seiberling Street • Akron, Ohio 44305

4 FIRST AID MEASURES

SKIN

Wash with soap and water. Get medical attention if irritation develops or persists.
HOT MOLTEN product: Immediately cool skin burns with water and cold packs for at least 15 minutes. Do NOT put ice directly on the skin. Do NOT attempt to remove solidified resin from the skin as severe tissue damage may result. Get immediate medical attention. See Note to Physician.

EYE

Remove contact lenses. Hold eyelids apart. Immediately flush eyes with plenty of low-pressure water for at least 15 minutes. Get medical attention if irritation persists.
HOT MOLTEN product: Cool burns with plenty of low-pressure water. Get immediate medical attention.

INHALATION

Remove to fresh air. Get medical attention if nasal, throat or lung irritation develops.

INGESTION

No adverse health effects are expected from accidental ingestion of small amounts of this product. For ingestion of large amounts: If conscious, drink one to two glasses of water (8-16 oz.). Do not induce vomiting. Get immediate medical attention. Never give anything by mouth to an unconscious person.

NOTES TO PHYSICIAN

For HOT MOLTEN or HOT LIQUID product: Material should not be forcibly pulled from the skin. Mineral oil may be used to loosen and soften the material.

5 FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

Water spray, dry chemical, foam, carbon dioxide or clean extinguishing agents may be used on fires involving this product.

FIRE FIGHTING PROCEDURES

Wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH approved (or equivalent) and full protective gear when fighting fires involving this product.

CONDITIONS TO AVOID

None known.

HAZARDOUS COMBUSTION PRODUCTS

If heated to combustion, the following substances may be formed: carbon monoxide, carbon dioxide aldehydes, carboxylic acids and smoke

FLASH POINT 500 ° F

6 ACCIDENTAL RELEASE MEASURES

If product is not contaminated, scoop into clean containers for use. Avoid wetting spills, as surfaces can become very slippery. If product is contaminated, scoop into containers, and dispose appropriately. In case of accidental spill or release, refer to Section 8, Personal Protective Equipment and General Hygiene Practices.

This product contains a petroleum hydrocarbon. Prevent runoff from spills or leaks entering navigable waters, streams or other bodies of water. If runoff occurs, notify the National Response Center (NRC) at 800-424-8802.

7 HANDLING & STORAGE

GENERAL MEASURES

Ground all equipment.

Blanket vessel with inert gas when emptying bags where flammable vapors may be present.

Ground operator and pour material slowly into conductive, grounded chute.

For large bags (1000 lbs or greater) a ground cable **MUST** be attached to the bag ground connection.

Store in a cool, dry, well-ventilated area at approximately 20° C (68° F).

Keep container closed when not in use.

Control inventory.

Rotate stock periodically.

For HOT MOLTEN or HOT LIQUID product: Use personal protective equipment as indicated in Section 8:

Exposure Controls/Personal Protection.

MATERIALS OR CONDITIONS TO AVOID

Avoid conditions that generate dust; product may form flammable dust-air mixtures.

Avoid emptying package in or near flammable vapors; static charges may cause flash fire.

Keep away from heat, flame, sparks and other ignition sources.

8 EXPOSURE CONTROLS / PERSONAL PROTECTION

WORK PRACTICES & ENGINEERING CONTROLS

Eyewash fountains and safety showers should be easily accessible.

Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Discharge from the ventilation system should comply with applicable air pollution control regulations.

Keep floors clean and dry. Clean up spills immediately.

GENERAL HYGIENIC PRACTICES

Avoid breathing dust, vapor or mist.

Avoid contact with eyes, skin, and clothing.

Avoid contamination of food, beverages, or smoking materials.

Wash thoroughly after handling, and before eating, drinking or smoking.

Remove contaminated clothing promptly and clean thoroughly before reuse.

RECOMMENDED EXPOSURE LIMITS

PARTICULATES (dust): If used under conditions that generate particulates (dust), the OSHA TWA of 5 mg/m³ respirable fraction (15 mg/m³ total), and ACGIH TLV-TWA of 3 mg/m³ respirable fraction (10 mg/m³ total) should be observed.

PERSONAL PROTECTIVE EQUIPMENT

Safety glasses

Impervious gloves

Appropriate protective clothing

Appropriate respiratory protection is required when exposure to airborne contaminants may exceed acceptable limits. Respirators should be selected and used in accordance with OSHA, Subpart I (29 CFR 1910.134) and manufacturers recommendations.

Personnel exposed to HOT MOLTEN or HOT LIQUID material should wear protective clothing that provides protection against thermal burns. Required Protective Equipment: a) Longsleeved protective shirt, long pants, and work shoes; b) Hard hat and face shield; c) Long-cuff gloves (Gauntlet type-extending beyond the wrist); d) Lined rainsuit with protective hood or shoulder shroud or e) Full aluminized or thermal suit with hood.

PROTECTIVE MEASURES DURING REPAIR AND MAINTENANCE

Eliminate ignition sources and prevent build-up of static electrical charges.

Completely isolate and thoroughly clean all equipment, piping, or vessels before beginning maintenance or repairs.

Keep area clean. Product will burn.

9 PHYSICAL & CHEMICAL PROPERTIES

PHYSICAL STATE:	solid or flake
COLOR:	amber
ODOR:	hydrocarbon
Specific Gravity	1.07
Percent Volatile	negligible at 68° F
Evaporation Rate	slower than butyl acetate
Solubility In Water	negligible at 68° F
Softening Point	239 ° F

10 STABILITY & REACTIVITY

HAZARDOUS DECOMPOSITION PRODUCTS

None known.

HAZARDOUS POLYMERIZATION

Not anticipated under normal or recommended handling and storage conditions.

GENERAL STABILITY CONSIDERATIONS

Stable under recommended handling and storage conditions.

INCOMPATIBLE MATERIALS

None known

11 TOXICOLOGICAL INFORMATION

CARCINOGENICITY INFORMATION

Not listed as a carcinogen by NTP. Not regulated as a carcinogen by OSHA. Not evaluated by IARC.

REPORTED HUMAN EFFECTS

No human toxicity studies have been carried out with this product. Due to the physical nature of this material, may cause eye, skin and respiratory irritation.

REPORTED ANIMAL EFFECTS

No animal toxicity studies have been carried out with this product.

COMPONENT - hydrocarbon resin: Not toxic by OSHA/ANSI criteria based on acute animal peroral testing of this or a similar product (LD50 >500 mg/kg). Necropsy revealed effects on rat kidneys at test levels >1 g/kg.

MUTAGENICITY/GENOTOXICITY INFORMATION

No mutagenicity studies have been carried out with this product.

12 ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL INFORMATION

No ecological studies have been carried out on this product.

13 DISPOSAL CONSIDERATIONS

WASTE DISPOSAL

Landfilling in a permitted solid or hazardous waste facility is recommended. Handling, transportation, and disposal of material should be conducted in a manner to prevent a nuisance dust hazard. Fully containerize the material before handling, and protect from exposure to the outdoors. Ensure there are no restrictions on disposing of bulk or semi-bulk quantities of waste material. Disposal should be in accordance with all Federal, State and local regulations.

14 TRANSPORT INFORMATION

GENERAL

This product is not subject to DOT, ICAO, IMDG or ADR regulations.

For specific information regarding transportation of this product, please contact the Hercules Transportation Department at (302) 594-7356 or FAX at (302) 594-7256.

15 REGULATORY INFORMATION

CHEMICAL INVENTORIES

U.S. TSCA: The components of this product are included on the TSCA Inventory.

SARA TITLE III - SECTION 302/304

This product is not an Extremely Hazardous Substance subject to reporting under 40CFR355.

SARA TITLE III - SECTION 311 AND 312

NHH: Not a health hazard

HC-3: Fire hazard

SARA TITLE III - SECTION 313

This product does not contain any chemicals subject to reporting under Section 313 of Title III of the Superfund Amendments and Reauthorization Act and 40CFR372.

CERCLA

This product does not contain any chemicals subject to reporting as a CERCLA Hazardous Substance under 40CFR302.4.

RCRA

This product is not a hazardous waste as listed in 40CFR261.33. It does not exhibit any of the hazardous characteristics listed in 40CFR261, Subpart C.

16 OTHER INFORMATION

HMIS RATINGS:

Health	0	Minimal Hazard
Flammability	1	Slight Hazard
Reactivity	0	Minimal Hazard

LIST OF ACRONYMS

ACGIH: American Conferences of Governmental Industrial Hygienists
AIHA WEEL: American Industrial Hygienists Association-Workplace Environmental Exposure Level
ANSI: American National Standards Institute
CASRN: Chemical Abstracts Service Registry Number
CEPA: Canadian Environmental Protection Act
CERCLA: Comprehensive Emergency Response, Compensation and Liability Act
DSL: Domestic Substances List (Canadian)
HMIS: Hazardous Materials Identification System
IARC: International Agency for Research on Cancer
NDSL: Non-Domestic Substances List (Canadian)
NTP: National Toxicology Program
OSHA: Occupational Safety and Health Administration
PEL: Permissible Exposure Limit (OSHA)
RCRA: Resource Conservation and Recovery Act
RQ: Reportable Quantity
SARA: Superfund Amendment Reauthorization Act
STEL: Short-Term Exposure Limit
TLV: Threshold Limit Values (registered trademark of ACGIH)
TPQ: Threshold Planning Quantity
TSCA: Toxic Substance Control Act
TWA: Time Weighted Average

DISCLAIMER

The information and recommendations contained in this Material Safety Data Sheet have been compiled from sources believed to be reliable and to represent the most reasonable current opinion on the subject when the MSDS was prepared. No warranty, guaranty or representation is made as to the correctness or sufficiency of the information. The user of this product must decide what safety measures are necessary to safely use this product, either alone or in combination with other products, and determine its environmental regulatory compliance obligations under any applicable federal or state laws.