

# EASTMAN

## MATERIAL SAFETY DATA SHEET

Revision Date: 05/18/2005

MSDSUSA/ANSI/EN/150000049590/Version 5.1

### 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

<b>Product Name</b>	Picco(TM) 5140 Hydrocarbon Resin
<b>Product Identification Number(s)</b>	5140, P7520000, P7520001, P752000Q, P752000R, P7520002, P752000B, P752000X, P75200SP, P7520006, E7520001, P75200TR, P75200TS
<b>Manufacturer/Supplier</b>	Eastman Chemical Company 200 South Wilcox Drive Kingsport, TN 37660-5280 US +14232292000
<b>MSDS Prepared by</b>	Eastman Product Safety and Health
<b>Chemical Name</b>	not applicable
<b>Synonym(s)</b>	75200-00 800238
<b>Molecular Formula</b>	not applicable
<b>Molecular Weight</b>	not applicable
<b>Product Use</b>	industrial chemical
<b>OSHA Status</b>	nonhazardous

For emergency health, safety & environmental information, call 800-EASTMAN.

For emergency transportation information, call CHEMTREC at 800-424-9300 or call 800-EASTMAN.

### 2. COMPOSITION INFORMATION ON INGREDIENTS

*(Typical composition is given, and it may vary. A certificate of analysis can be provided, if available.)*

<u>Weight %</u>	<u>Component</u>	<u>CAS Registry No.</u>
99 - 100%	hydrocarbon resin	68131-77-1
0 - 1%	residual additives, modifiers, colorants, reactants, and/or impurities	not applicable

### 3. HAZARDS IDENTIFICATION

#### WARNING!

STATIC CHARGES GENERATED BY EMPTYING PACKAGE IN OR NEAR FLAMMABLE VAPOR  
MAY CAUSE FLASH FIRE  
POWDERED MATERIAL MAY FORM EXPLOSIVE DUST-AIR MIXTURES  
MOLTEN MATERIAL WILL PRODUCE THERMAL BURNS

**HMIS® Hazard Ratings:** Health - 1, Flammability -1, Chemical Reactivity - 0

©COPYRIGHT 2005 BY EASTMAN CHEMICAL COMPANY

Visit our website at [www.EASTMAN.com](http://www.EASTMAN.com) or call 001-423-229-2000.

Page 1

MARKETED BY  
**HARWICK STANDARD**  
DISTRIBUTION CORPORATION  
60 S. Selberling Street • Akron, Ohio 44305

# EASTMAN

## MATERIAL SAFETY DATA SHEET

Revision Date: 05/18/2005

MSDSUSA/ANSI/EN/150000049590/Version 5.1

*HMIS® rating involves data interpretations that may vary from company to company. They are intended only for rapid, general identification of the magnitude of the specific hazard. To deal adequately with the safe handling of this material, all the information contained in this MSDS must be considered.*

### 4. FIRST-AID MEASURES

**Inhalation:** If symptomatic, move to fresh air. Get medical attention if symptoms persist.

**Eyes:** If molten material contacts the eye, immediately flush with plenty of water for at least 15 minutes. Get medical attention immediately.

**Skin:** If burned by contact with molten material, cool as quickly as possible. Do not peel material from skin. Get medical attention.

**Ingestion:** Seek medical advice.

**Note to Physicians:** Burns should be treated as thermal burns. The material will come off as healing occurs; therefore, immediate removal from the skin is not necessary.

### 5. FIRE FIGHTING MEASURES

**Extinguishing Media:** water spray, dry chemical, carbon dioxide

**Special Fire-Fighting Procedures:** Wear self-contained breathing apparatus and protective clothing.

**Hazardous Combustion Products:** carbon dioxide, carbon monoxide

**Unusual Fire and Explosion Hazards:** Powdered material may form explosive dust-air mixtures.

**Sensitivity to Static Discharge:** Static charges generated by emptying package in or near flammable vapors may cause flash fire.

### 6. ACCIDENTAL RELEASE MEASURES

Sweep or scoop up and remove.

### 7. HANDLING AND STORAGE

**Personal Precautionary Measures:** Avoid contact with molten material.

**Prevention of Fire and Explosion:** Keep away from heat, sparks, and flame. Keep from contact with oxidizing materials. Minimize dust generation and accumulation. In the United States of America, refer to NFPA® Pamphlet No. 654, "Prevention of Fire and Dust Explosions in the Chemical, Dye, Pharmaceutical, and Plastics Industries."

**Storage:** Keep container closed. Store in a cool place.

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

*Country specific exposure limits have not been established or are not applicable unless listed below.*

**Ventilation:** Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. Supplementary local exhaust ventilation, closed

# EASTMAN

## MATERIAL SAFETY DATA SHEET

Revision Date: 05/18/2005

MSDSUSA/ANSI/EN/150000049590/Version 5.1

systems, or respiratory and eye protection may be needed in special circumstances; such as poorly ventilated spaces, heating, evaporation of liquids from large surfaces, spraying of mists, mechanical generation of dusts, drying of solids, etc.

**Respiratory Protection:** If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. In the United States of America, if respirators are used, a program should be instituted to assure compliance with OSHA Standard 63 FR 1152, January 8, 1998. Respirator type: Air-purifying respirator with an appropriate, government approved (where applicable), air-purifying filter, cartridge or canister. Contact health and safety professional or manufacturer for specific information.

**Eye Protection:** Wear a face shield when working with molten material.

**Skin Protection:** When material is heated, wear gloves to protect against thermal burns.

**Recommended Decontamination Facilities:** eye bath, washing facilities

### 9. PHYSICAL AND CHEMICAL PROPERTIES

**Physical Form:** solid

**Color:** amber

**Odor:** hydrocarbon

**Specific Gravity:** 1.07

**Softening Point:** 140 - 145 °C

**Solubility in Water:** negligible

**Flash Point:** not applicable, combustible solid

**Thermal Decomposition Temperature:** Thermal stability not tested. Low stability hazard expected at normal operating temperatures.

### 10. STABILITY AND REACTIVITY

**Stability:** Not fully evaluated. Materials containing similar structural groups are normally stable.

**Incompatibility:** Material reacts with strong oxidizing agents.

**Hazardous Polymerization:** Will not occur.

### 11. TOXICOLOGICAL INFORMATION

*Acute toxicity data, if available, are listed below. Additional toxicity data may be available on request.*

### 12. ECOLOGICAL INFORMATION

*Acute toxicity data, if available, are listed below. Additional toxicity data may be available on request.*

This material has not been tested for environmental effects.

# EASTMAN

## MATERIAL SAFETY DATA SHEET

Revision Date: 05/18/2005

MSDSUSA/ANSI/EN/150000049590/Version 5.1

### 13. DISPOSAL CONSIDERATIONS

Discharge, treatment, or disposal may be subject to national, state, or local laws. Incinerate.

### 14. TRANSPORT INFORMATION

*Important Note: Shipping descriptions may vary based on mode of transport, quantities, package size, and/or origin and destination. Consult your company's Hazardous Materials/Dangerous Goods expert for information specific to your situation.*

#### DOT (USA)

Class not regulated

#### Sea - IMDG (International Maritime Dangerous Goods)

Class not regulated

#### Air - ICAO (International Civil Aviation Organization)

Class not regulated

### 15. REGULATORY INFORMATION

**This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.**

**WHMIS (Canada) Status:** noncontrolled

**SARA 313:** none, unless listed below

**Carcinogenicity Classification (components present at 0.1% or more):** none, unless listed below

---

©COPYRIGHT 2005 BY EASTMAN CHEMICAL COMPANY

Visit our website at [www.EASTMAN.com](http://www.EASTMAN.com) or call 001-423-229-2000.

# EASTMAN

## MATERIAL SAFETY DATA SHEET

Revision Date: 05/18/2005

MSDSUSA/ANSI/EN/150000049590/Version 5.1

**TSCA (US Toxic Substances Control Act):** All components of this product are listed on the TSCA inventory. Any impurities present in this product are exempt from listing.

**DSL (Canadian Domestic Substances List) and CEPA (Canadian Environmental Protection Act):** All components of this product are listed on the DSL. Any impurities present in this product are exempt from listing.

**EINECS (European Inventory of Existing Commercial Chemical Substances):** All components of this product are listed on EINECS. Any polymer present in this product has regulatory clearance under Directives of the European Union.

**AICS / NICNAS (Australian Inventory of Chemical Substances and National Industrial Chemicals Notification and Assessment Scheme):** All components of this product are listed on AICS or otherwise comply with NICNAS.

**MITI (Japanese Handbook of Existing and New Chemical Substances):** All components of this product are listed in the Handbook or have been approved in Japan by new substance notification.

**ECL (Korean Toxic Substances Control Act):** All components of this product are listed on the Korean inventory or otherwise comply with the Korean Toxic Substances Control Act.

**Phillipines Inventory (PICCS) :** All components of this product are listed on the Phillipine inventory or otherwise comply with PICCS.

### 16. OTHER INFORMATION

Visit our website at [www.EASTMAN.com](http://www.EASTMAN.com) or call 001-423-229-2000.

*The information contained herein is based on current knowledge and experience; no responsibility is accepted that the information is sufficient or correct in all cases. Users should consider these data only as a supplement to other information. Users should make independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials, the safety and health of employees and customers, and the protection of the environment.*

*Highlighted areas indicate new or changed information.*