

Product Name CALIFLUX LP

Page 1

HMIS Rating: Health Fire 1 Reactivity

NFPA Rating: Toxicity: 1 Fire: 1 Reactivity: 0  
(4=Extreme, 3=High, 2=Moderate, 1=Slight, 0=Insignificant)

=====

COMPANY NAME AND LOCATION - SECTION I

=====

Company : Golden Bear.  
Location: Oildale, Ca.  
P.O. BOX 5446, 1134 Manor Street, Oildale, Ca, 93388-5446.  
Emergency Telephone Number: (661) 393-7110.  
Transportation Emergency: CHEM TREC 800) 424-9300 (U.S. and Canada)

=====

CHEMICAL AND PHYSICAL PROPERTIES---SECTION II

=====

Chemical Name: Petroleum hydrocarbon.  
Formula: Not applicable.  
Hazardous Decomposition Products:  
Carbon monoxide and carbon dioxide from burning.  
Oxides of nitrogen.  
Oxides of sulfur.  
Incompatibility (Keep away from):  
Strong oxidizers such as hydrogen peroxide, bromine, and chromic acid  
Toxic and Hazardous Ingredients: CAS #  
Light naphthenic extract (petroleum) 64742-03-6  
Form: Oily liquid.  
Odor: No objectionable odor  
Appearance:  
Color:  
Specific Gravity (water=1): 0.95 to 1.04.  
Boiling Point: Greater than 288 C (550 F).  
Melting Point: Not applicable.  
Solubility in Water: 0%.  
Volatile (by weight %): Less than 0.01 at 25 C.  
Evaporation Rate (water= 1) Less than 0.01.  
Vapor Pressure (mm Hg at 20 C) Less than 1.0.  
Vapor Density (air=1): No data available.  
pH (as is): Not applicable.  
Stability: Product is stable under normal conditions  
Viscosity SUS at 100 F: Greater than or equal to 100.  
Other Physical Properties: Viscosity greater than or equal to 8.6 cSt  
at 40 C.

(continued on next page)

MARKETED BY  
**HARWICK STANDARD**  
**DISTRIBUTION CORPORATION**  
60 S. Seiberling Street • Akron, Ohio 44305

=====

FIRE AND EXPLOSION DATA---SECTION III

=====

Special Fire Fighting Procedures:

Avoid use of water.

Unusual Fire and Explosion Hazards:

Dense smoke. Fire fighters should wear an approved self-contained breathing apparatus.

Flashpoint: (Method Used) Cleveland Open Cup greater than 149 C (300 F).

Flammable limits %: No data available.

Extinguishing agents:

Drychemical or Waterspray or CO2 or Foam.

Water may cause frothing.

Water may be ineffective.

Closed containers exposed to fire may be cooled with water.

=====

HEALTH HAZARD DATA---SECTION IV

=====

Permissible concentrations (air):

If used in applications where a mist may be generated, observe a TWA/PEL of 5 mg/m3 for mineral oil mist (OSHA and ACGIH).

Chronic effects of overexposure:

Prolonged skin contact may cause irritation and under extreme conditions, skin cancer. See Comments section.

Acute toxicological properties: No data available.

Emergency First Aid Procedures:

Eyes: Immediately flush with large quantities of water for at least 15 minutes and call a physician.

Skin Contact: Wash with soap and water.

Inhalation: Remove victim to fresh air.

If Swallowed: Contact a physician immediately.

ROUTES OF ENTRY:

Ingestion and, if a mist is generated, inhalation.

TARGET ORGAN(S):

Skin. Respiratory tract if a mist is generated. (The respiratory tract may become irritated).

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE:

Persons susceptible to dermatitis (skin rash) may aggravate their condition by skin contact with this product.

=====

SPECIAL PROTECTION INFORMATION---SECTION V

=====

Ventilation Type Required (Local, mechanical, special):

Local if necessary to maintain allowable PEL (permissible exposure limit) or TLV (threshold limit value)

Respiratory Protection (Specify type):

Use NIOSH/MSHA certified respirator with organic vapor cartridge if vapor concentration exceeds permissible exposure limit.

Protective Gloves: Oil resistant.

Eye Protection: Chemical safety goggles and, if used hot, full face shield.

Other Protective Equipment: None.

(Continued on next page)

=====

HANDLING OF SPILLS OR LEAKS---SECTION VI

=====

Procedures for Clean-Up:

In case of spill or leak absorb on an inert material such as earth, sand or vermiculite; sweep up and dispose of in accordance with federal, state and local regulations. If spilled into water, remove bulk of the product by skimming. If spilled into a navigable waterway and a film, sheen or discoloration of any water surface is noted, the spill must be reported to the National Response Center by calling (800) 424-8802.

Waste Disposal:

Dispose of in accordance with all applicable federal, state and local regulations.

=====

SPECIAL PRECAUTIONS---SECTION VII

=====

Precautions to be taken in handling and storage:

Avoid prolonged or repeated contact with skin or breathing of vapors, mists or fumes. Launder contaminated clothing before reuse. Keep containers tightly closed. Avoid strong oxidizers. Eliminate all sources of ignition such as flames or sparks.

=====

TRANSPORTATION DATA---SECTION VIII

=====

D.O.T.: Regulated.

U.S. D.O.T. Proper Shipping Name: Elevated temperature liquid, n.o.s.

(at or above 100C (212F) and below its flash point), (petroleum oil).

U.S. D.O.T. Hazard Class: 9.

I.D. Number: UN 3257; PG III.

Label(s) Required: Mark as HOT.

Reportable Quantity: Not applicable.

Freight Classification: 65 Petroleum Oil, n.o.i.b.n.

Special Transportation Notes:

If shipped in containers of over 118.9 gallon capacity and above 100C (212F), regulated as an elevated temperature liquid, n.o.s. (at or above 100C(212F) and below its flash point), (petroleum oil). Mark: HOT, ID.NO.3257.

-----  
ENVIRONMENTAL/SAFETY REGULATIONS---SECTION IX  
-----

Section 313 (Title III Superfund Amendment and Reauthorization Act):  
This product does not contain any chemical subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

-----  
COMMENTS  
-----

This product contains petroleum oils similar to ones categorized by the International Agency for Research on Cancer (IARC) as causing skin cancer in mice after prolonged and repeated contact. Any potential hazard can be minimized by using recommended protective equipment to avoid skin contact and by washing thoroughly after handling.

Approved by: J.L. Davis, Laboratory Director

Original Date: 07/16/97

Revision Date: 03/01/99

Supersedes: 07/16/97.

-----  
We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind, express or implied, and we assume no responsibility for any loss, damage, or expense, direct or consequential, arising out of their use.