Natro-Cel™ BCF-A

1: Identification

Product identifier: Natro-Cel™ BCF-A

Other means of identification: Dibutoxyethoxyethyl formal on silicon dioxide

Supplier:

P.O. Sava

NATROCHEM, Inc. P.O. Box 1205

Savannah, GA 31402-1205

912-236-4464

Recommended use: Rubber plasticizer **Restrictions on use:** Not applicable.

Emergency phone number: CHEMTREC (USA) 800-424-9300 CHEMTREC (Int'l) 202-483-7616

2: Hazard(s) identification

OSHA/HCS status: While this material is not considered hazardous by the OSHA Hazard

Communication Standard (29 CFR 1910.1200), this SDS contains valuable information critical to the safe handling and proper use of

the product. This SDS should be retained and available for

employees and other users of this product.

GHS classification: Not classified.

GHS label elements

Signal word: WARNING
Symbol(s):



Hazard statements:

Hazards not otherwise

classified:

May form combustible dust concentrations in the air.

Precautionary statements:

Prevention: Avoid breathing dust/vapours.

Do not get in eyes, on skin, or on clothing.

Do not eat, drink or smoke when using this product.

Avoid release to the environment.

Response: IF ON SKIN (or hair): Wash with plenty of soap and water.

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

IF INHALED: Remove person to fresh air and keep comfortable for

breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses if present and easy to do – continue rinsing.

IF exposed or concerned: Call a POISON CENTER/ doctor if you feel

unwell.

In case of fire: Use CO₂, dry chemical, water spray, or foam to

extinguish.

Storage: Store in a dry place. Store in a closed container.

Disposal: Dispose of contents/container in accordance with applicable

regulations.

Supplemental information: Not applicable.

3: Composition

Substance/mixture: Mixture

Ingredient	Synonyms	CAS number	Concentration (%)
Hexaoxatricosane		143-29-3	65-74
Diethylene glycol monobutyl ether		112-34-5	1-4
Silica, amorphous, precipitated, and gel		112926-00-8	26-30

Contains no detectable crystalline silica (detection limit <0.01% by weight)

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

4: First-aid measures

If ingestion, irritation, any type of overexposure or symptoms of overexposure occur during or persists after use of this product, contact a POISON CONTROL CENTER, EMERGENCY ROOM, OR PHYSICIAN immediately; have SDS information available. Never give anything by mouth to an unconscious or convulsing person.

Description of necessary first aid measures

Eye contact: Check for and remove any contact lenses. Immediately flush eyes

with running water for at least 15 minutes, keeping eyelids open.

Seek immediate medical attention.

Inhalation: Remove to fresh air. Keep person warm and at rest. If not breathing,

if breathing is irregular, or if respiratory arrest occurs, provide

artificial respiration or oxygen by trained personnel.

Skin contact: Remove contaminated clothing and shoes. Wash skin thoroughly

with soap and water or use recognized skin cleanser. Do NOT use

solvents or thinners.

Ingestion: If swallowed, seek medical advice immediately and show this

container or label. Keep person warm and at rest. Do NOT induce

vomiting.

Most important symptoms/effects, acute and delayed.

Potential acute health effects

Eye contact: No significant irritation expected other than possible mechanical

irritation.

Inhalation: Exposure to airborne concentrations above statutory or

recommended exposure limits may cause irritation of the nose,

throat, and lungs.

Skin contact: Prolonged or repeated contact may dry skin and cause irritation.

Ingestion: No known significant effects or critical hazards.

Over-exposure signs/symptoms

Eye contact: Adverse symptoms may include the following:

Irritation Redness

Inhalation: Adverse symptoms may include the following:

Coughing

Respiratory tract irritation

Skin contact: Adverse symptoms may include the following:

Dryness

Ingestion: No specific data.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician: Treat symptomatically. Contact poison treatment specialist

immediately if large quantities have been ingested or inhaled.

Specific treatments: No specific treatment.

Protection of first-aiders: No action shall be taken involving any personal risk or without

suitable training.

See toxicological information (Section 11)

5: Fire-fighting measures

Extinguishing media

Suitable extinguishing media: Use CO₂, dry chemical, water spray, or foam.

Unsuitable extinguishing Do not use a solid water stream as it may scatter and spread fire.

media:

Specific hazards arising from

the chemical:

Product forms a slippery surface when combined with water.

Hazardous thermal In the event of a fire, hazardous decomposition products may

decomposition products: include:

Carbon monoxide Carbon dioxide

Other unidentified organic compounds

Special protective actions for No action shall be taken involving any personal risk or without

firefighters: proper training.

Special protective equipment Firefighters and others who may be exposed to products of

for firefighters: combustion should wear full firefighting turn out gear (full bunker gear) and self-contained breathing apparatus (SCBA) operated in

pressure-demand mode (MSHA/NIOSH approved or equivalent).

6: Accidental release measures

Personal precautions, protective equipment, and emergency procedures

For non-emergency Keep unnecessary and unprotected personnel from entering. Do not

touch or walk through spilled material. Product forms slippery personnel: surface when combined with water. No action shall be taken

involving any personal risk or without suitable training.

For emergency responders: If specialized clothing is required to deal with the spillage, take note

> of any information in Section 8 on suitable and unsuitable materials. See also the information immediately above in "For non-emergency

personnel".

Environmental precautions: Avoid release to sewers, waterways, soil, or air. Inform the relevant

authorities if the product has caused environmental pollution

(sewers, waterways, soil, or air).

Methods and materials for containment and cleaning up

Small spill: Avoid generating dust. Vacuum or sweep up material and place in a

designated, labeled waste container.

Avoid generating dust. Vacuum or sweep up material and place in a Large spill:

designated, labeled waste container.

See Section 1 for emergency contact information.

See Section 8 for information on appropriate personal protective equipment.

See Section 13 for additional waste treatment information.

7: Handling and storage

Precautions for safe handling

Protective measures: Put on appropriate personal protective equipment (see **Section 8**). Advice on general Eating, drinking, and smoking should be prohibited in areas where occupational hygiene: this material is handled, stored, and processed. Workers should

> wash hands and face before eating, drinking, and smoking. Remove contaminated clothing and protective equipment before entering eating areas. When transferring material into flammable solvents, use proper grounding to avoid electrical sparks. Avoid alteration of product properties before use. Calcining (which may result in

toxicological properties.

See also **Section 8** for additional information on hygiene measures.

crystalline silica formation) or mixing with additives may alter

Conditions for safe storage, Store in accordance with local regulations. Store in original container including any incompatibilities:

protected from direct sunlight in a dry, cool, and well-ventilated area away from incompatible materials (see **Section 10**) and food and drink. Keep container tightly closed and sealed until ready for use. Do not store in unlabeled containers.

8: Exposure controls/personal protection

Control parameters

Occupational exposure limits

occupational exposure iiii	occupational exposure mints				
Components with limit values that require monitoring at the workplace:					
Diethylene glycol monobuty	l ether (112-34-5)				
ACGIH TLV	10 ppm inhalable fraction and vapour TWA				
Recommended monitoring	If this product contains ingredients with exposure limits, personal,				
procedures:	workplace atmosphere, or biological monitoring may be required to				
	determine the effectiveness of the ventilation or other control				
	measures and/or the necessity to use respiratory protective				
	equipment. Reference should be made to appropriate monitoring				
	standards. Reference to national guidance documents for methods				
	for the determination of hazardous substances will also be required.				
Appropriate engineering	Good general ventilation should be sufficient to control worker				
controls:	exposure to airborne contaminants.				
Environmental exposure	Emissions from ventilation or work process equipment should be				
controls:	checked to ensure that they comply with the requirements of				
	environmental protection legislation. In some cases, fume scrubbers,				
	filters, or engineering modifications to process equipment will be				
	necessary to reduce emissions to acceptable levels.				

Individual protection measures

Hygiene measures:	wash hands, forearms, and face thoroughly after handling chemical
	products, before eating, smoking, and using the lavatory, and at the
	and of the working period. Appropriate techniques should be used to

end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety

showers are close to the workstation location.

Eye/face protection: Safety eyewear complying with an approved standard should be

used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases, or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: splash goggles.

Skin protection

Hand protection: Chemical-resistant, impervious gloves complying with an approved

standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. When handling hot material, wear heat-resistant gloves that are able to

withstand the temperature of molten product.

Body protection: Personal protective equipment for the body should be selected

based on the task being performed and the risks involved and should

be approved by a specialist before handling this product.

Other skin protection: Appropriate footwear and any additional skin protection measures

should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this

product.

Respiratory protection: Respirator selection must be based on known or anticipated

exposure levels, the hazards of the product and the safe working

limits of the selected respirator. If workers are exposed to

concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment

indicates this is necessary.

9: Physical and chemical properties

Appearance

Physical state: Powder, solid, or granular solid.

Color: White to off-white.

Odor: Mild.

Not available. Odor threshold: pH: Not available. Melting/freezing point: Not available. **Boiling point and range:** Not available. Flash point: Not available. **Evaporation rate:** Not available. Flammability: Not available. Flammability or explosive Not available.

limits:

Vapor pressure:Not available.Vapor density:Not available.Relative density:Not available.Solubility:Not available.Partition coefficient: n-Not available.

octanol/water:

Auto-ignition temperature: Not available.

Decomposition temperature: Not available.

Viscosity: Not applicable.

10: Stability and reactivity

Reactivity: No specific test data related to reactivity available for this product or

its ingredients.

Chemical stability: This product is stable.

Possibility of hazardous Under normal conditions of storage and use, hazardous reactions

reactions: will not occur.

Conditions to avoid: High temperature (>800°C) treatment (calcining), which may result in

crystalline silica formation.

Avoid alteration of product properties before use. Calcining or

mixing with additives may alter toxicological properties.

Avoid generating dust.

Refer to protective measures listed in Sections 7 and 8.

Incompatible materials: Reactive or incompatible with the following materials:

Acids

Oxidizing materials

Strong alkalis

Hazardous decomposition

In the event of a fire, hazardous decomposition products may

products: include:

Carbon monoxide Carbon dioxide

Other unidentified organic compounds

11: Toxicological information

Information on toxicological effects

Acute toxicity

Conclusion/summary: No known significant effects or critical hazards.

Ingredient	Result	Species	Dose	Exposure
Hexaoxatricosane	LD ₅₀ oral	Rat	1746 mg/kg	-
Diethylene glycol	LD ₅₀ oral	Rat	3384 mg/kg	-
monobutyl ether	LD ₅₀ dermal	Rabbit	2700 mg/kg	-

Irritation/corrosion

Conclusion/summary

Skin: No known significant effects or critical hazards. No known significant effects or critical hazards. Eyes: **Respiratory:** No known significant effects or critical hazards.

Sensitization

Conclusion/summary:

Skin: No known significant effects or critical hazards. Respiratory: No known significant effects or critical hazards.

Mutagenicity:

Conclusion/summary: No known significant effects or critical hazards.

Carcinogenicity

Conclusion/summary: No known significant effects or critical hazards.

Classification

Ingredient	OSHA	IARC	NTP
Silica, amorphous,	-	3	1
precipitated, and gel			

Carcinogen classification code:

IARC: 1, 2A, 2B, 3, 4

NTP: [Known/Reasonably anticipated] to be a human carcinogen

OSHA: +

Not listed/regulated: -

Reproductive toxicity

Conclusion/summary: No known significant effects or critical hazards.

Teratogenicity

Conclusion/summary: No known significant effects or critical hazards.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Target organs Contains material which may cause damage to the following organs:

upper respiratory tract, eyes.

Aspiration hazard

Not available.

Information on the likely routes Routes of entry anticipated: oral, dermal, inhalation.

of exposure:

Potential acute health effects

Eye contact: No significant irritation expected other than possible mechanical

irritation.

Inhalation: Exposure to airborne concentrations above statutory or

recommended exposure limits may cause irritation of the nose,

throat, and lungs.

Skin contact: Prolonged or repeated contact may dry skin and cause irritation.

Ingestion: No known significant effects or critical hazards.

Symptoms related to the physical, chemical, and toxicological characteristics

Eye contact: Adverse symptoms may include the following:

Irritation Redness

Inhalation: Adverse symptoms may include the following:

Coughing

Respiratory tract irritation

Skin contact: Adverse symptoms may include the following:

Dryness

Ingestion: No specific data.

Delayed and immediate effects and also chronic effects from short- and longterm exposure

Conclusion/summary: An epidemiological study was conducted which included 165

precipitated silica workers who had been exposed an average time of 8.6 years. Of these 165 workers, 44 had been exposed for an average of 18 years. No adverse effects were noted in complete medical examinations (including chest roentgenograms) of these workers. Pulmonary function decrements were correlated only with smoking and age but not with the degree or duration of dust exposures. Laboratory studies have also been conducted in small animals via inhalation of levels of precipitated silica dust of up to 126 mg/m³ per periods from six months to two years. Although precipitated silica was temporarily deposited in animals' lungs, most of the deposited material was cleared soon after the dust exposure ended. The results

of all studies performed by, or known to, PPG indicated a very low order of pulmonary activity for synthetic precipitated silicas. PPG recommends that persons with breathing problems or lung disease should not work in dusty areas unless a physician approves and certifies their fitness to wear respiratory protection.

Short-term exposure

Potential immediate No significant irritation expected other than possible mechanical

effects irritation.

Potential delayed effects Prolonged or repeated contact may dry skin and cause irritation.

Long-term exposure

Potential immediate Repeated or prolonged inhalation of dust may lead to chronic

effects respiratory irritation.

Potential delayed effects Repeated or prolonged inhalation of dust may lead to chronic

respiratory irritation.

Potential chronic health effects

General:No known significant effects or critical hazards.Carcinogenicity:No known significant effects or critical hazards.Mutagenicity:No known significant effects or critical hazards.Teratogenicity:No known significant effects or critical hazards.Developmental effects:No known significant effects or critical hazards.Fertility effects:No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Not available.

12: Ecological information

Toxicity

Ingredient	Result	Species	Exposure
Silica, amorphous,	NOEC > 1000 ppm	Daphnia – daphnia magna	24 hours
precipitated, and gel	Acute NOEC > 10000 ppm fresh	Fish	96 hours static
	water		
	Acute NOEC > 10000 ppm	Fish – brachydanio rerio	4 days static
Diethylene glycol	EC50 100 mg/L	Algae – desmodesmus	96 hours
monobutyl ether		subspicatus	
	LC50 1300 mg/L	Fish – <i>lepomis</i>	96 hours static
		macrochirus	
	EC50 2850 mg/L	Daphnia – daphnia magna	24 hours
	EC50 100 mg/L	Daphnia – daphnia magna	48 hours

Persistence and degradability

Ingredient	Aquatic half-life	Photolysis	Biodegradability
Silica, amorphous,	-	-	Not readily

precipitated, and gel		
1 /		

Bioaccumulative potential

Ingredient	LogP _{ow}	BCF	Potential
Silica, amorphous,	-	0	low
precipitated, and gel			

Mobility in soil

Soil/water partition Not available.

coefficient (Koc):

Other adverse effects: No known significant effects or critical hazards.

13: Disposal considerations

Disposal methods: The generation of waste should be avoided or minimized wherever

possible. Disposal of this product, solutions, and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local

authority requirements.

Disposal should be in accordance with applicable regional, national, and local laws and regulations.

Refer to Sections 6, 7, and 8 for additional information on accidental release measures, handling and storage, and exposure controls.

14: Transport information

	DOT	IMDG	IATA
UN number	Not regulated.	Not regulated.	Not regulated.
UN proper shipping	-	-	-
name			
Transport hazard	-	-	-
class(es)			
Packing group	-	-	-
Environmental hazards	No.	No.	No.
Marine pollutant	Not applicable.	Not applicable.	Not applicable.
substances			
Additional information	-	-	-

Special precautions for user: Transport within user's premises: always transport in closed

containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an

accident or spillage.

Transport in bulk according to Annex II of MARPOL 73/78 and

Not available.

the IBC code:

15: Regulatory information

Inventory status

United States inventory (TSCA All components are listed or exempted.

8b):

Australia inventory (AICS):

Canada inventory (DSL):

China inventory (IECSC):

Europe inventory (REACH):

All components are listed or exempted.

All components are listed or exempted.

All components are listed or exempted.

Japan inventory (ENCS): Please contact your supplier for information on the inventory status

of this material.

Korea inventory (KECI): All components are listed or exempted.

New Zealand inventory (NZIoC): All components are listed or exempted.

Philippines inventory (PICCS): All components are listed or exempted.

United States

US Federal regulations:

SARA Title III

Section 302 – Extremely Hazardous Chemicals:

The components in this product are either not SARA Section 302 regulated or are regulated but present in negligible concentrations.

Section 311/312 - Hazard Categories:

Chronic health hazard

Section 313 - Toxic Chemicals:

This material does not contain any chemical components with known CAS numbers that exceed the threshold (de minimis) reporting levels established by SARA Title III, Section 313.

Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) – Reportable Quantity (RQ)

The components of this product are either not CERCLA regulated, regulated but present in negligible concentrations, or regulated with no assigned reportable quantity.

US State regulations:

California Prop. 65:

No components are subject to California Prop. 65.

16: Other information

Hazardous Material Identification System (USA)



Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on SDSs under 29 CFR 1901.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the Nation Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J.J.Keller 800-327-6868.

* - chronic effects

The customer is responsible for determining the PPE code for this material.

Key to abbreviations:

ATE Acute toxicity estimate
BCF Bioconcentration factor

GHS Globally Harmonized System of classification and labeling of chemicals

IATA International Air Transport Association

IBC Intermediate bulk container

IMDG International Maritime Dangerous Goods

LogPow Logarithm of the octanol/water partition coefficient

MARPOL 73/78 International convention for the Prevention of Pollution from Ships, 1973,

as modified by the Protocol of 1978. (MARPOL = marine pollution)

UN United Nations

Disclaimer:

The information and recommendations contained herein are based upon data that are believed to be accurate and reliable. However, since data, safety standards, and government regulations are subject to change and the conditions of handling and use, or misuse are beyond our control, Natrochem, Inc. makes no warranty express or implied, with respect to the completeness or continuing accuracy of the information contained herein and disclaims all liability for reliance thereon.

Application and performance information are provided only as a guide, since the conditions of use are beyond the control of Natrochem, Inc. Consequently, Natrochem makes no warranties, express or implied, with respect to the goods or use of the goods or the performance of the goods and makes no warranties of fitness for a particular purpose for merchantability. Buyer acknowledges that Natrochem will not be liable for consequential, incidental, direct or special damages arising directly or indirectly in respect to such goods or the use or failure thereof, whether based on breach of warranty, negligence, strict liability in tort or otherwise.