

**EXCEL POLYMERS LLC**  
**MATERIAL SAFETY DATA SHEET**



**STAN-TONE MB-25462 RED**

Version Number 1.1  
Revision Date 11/20/2009

Page 1 of 8  
Print Date 2/5/2010

**1. PRODUCT AND COMPANY IDENTIFICATION**

**EXCEL POLYMERS LLC**  
**14330 Kinsman Road, Burton, OH 44021**

Telephone : Product Stewardship (440) 834-4644  
Emergency telephone : **CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).**

Product name : STAN-TONE MB-25462 RED  
Product code : AD3000021660  
Chemical Name : Mixture  
CAS-No. : Mixture  
Product Use : Industrial Applications

**2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS**

| Components        | CAS-No.    | Weight percent |
|-------------------|------------|----------------|
| Calcium stearate  | 1592-23-0  | 1 - 5          |
| Calcium carbonate | 471-34-1   | 1 - 5          |
| Magnesium oxide   | 1309-48-4  | 1 - 5          |
| Stearic acid      | 57-11-4    | 1 - 5          |
| Talc              | 14807-96-6 | 1 - 5          |

**3. HAZARDS IDENTIFICATION**

**EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

**POTENTIAL HEALTH EFFECTS**

**Routes of Exposure:** : Inhalation, Ingestion, Skin contact

**Acute exposure**

Inhalation : Particulates, like other inert materials can be mechanically irritating.  
Ingestion : May be harmful if swallowed.  
Eyes : Particulates, like other inert materials can be mechanically irritating.  
Skin : Experience shows no unusual dermatitis hazard from routine handling.

**Chronic exposure** : Refer to Section 11 for Toxicological Information.

# EXCEL POLYMERS LLC

## MATERIAL SAFETY DATA SHEET



### STAN-TONE MB-25462 RED

Version Number 1.1  
Revision Date 11/20/2009

Page 2 of 8  
Print Date 2/5/2010

**Medical Conditions** : None known.  
**Aggravated by Exposure:**

#### 4. FIRST AID MEASURES

**Inhalation** : Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.

**Ingestion** : Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.

**Eyes** : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.

**Skin** : Wash off with soap and plenty of water. If skin irritation persists seek medical attention.

#### 5. FIRE-FIGHTING MEASURES

**Flash point** : not applicable

**Flammable Limits**

- Upper explosion limit : not applicable
- Lower explosion limit : not applicable

**Autoignition temperature** : not applicable

**Suitable extinguishing media** : Water spray, Dry powder, Foam, Carbon dioxide (CO<sub>2</sub>).

**Special Fire Fighting Procedures** : Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.

**Unusual Fire/Explosion Hazards** : Carbon dioxide (CO<sub>2</sub>), carbon monoxide (CO), oxides of nitrogen (NO<sub>x</sub>), other hazardous materials, and smoke are all possible.

#### 6. ACCIDENTAL RELEASE MEASURES

**Personal precautions** : Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.

**Environmental precautions** : Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.

**Methods for cleaning up** : Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.

#### 7. HANDLING AND STORAGE

**EXCEL POLYMERS LLC**  
**MATERIAL SAFETY DATA SHEET**



**STAN-TONE MB-25462 RED**

Version Number 1.1  
Revision Date 11/20/2009

Page 3 of 8  
Print Date 2/5/2010

- Handling : Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
- Storage : Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

- Respiratory protection : No personal respiratory protective equipment normally required when handling the product itself. See "Engineering Measures" section below for precautions to be taken when heating or processing this material.
- Eye/Face Protection : Safety glasses with side-shields
- Hand protection : Protective gloves
- Skin and body protection : Long sleeved clothing
- Additional Protective Measures : Safety shoes
- General Hygiene Considerations : Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
- Engineering measures : Heat only in areas with appropriate exhaust ventilation. Adequate ventilation and/or appropriate respiratory protection may also be necessary to minimize employee exposure to processing vapors.

Exposure limit(s)

**EXCEL POLYMERS LLC****MATERIAL SAFETY DATA SHEET****STAN-TONE MB-25462 RED**Version Number 1.1  
Revision Date 11/20/2009Page 4 of 8  
Print Date 2/5/2010

| Components        | Value     | Exposure time                     | Exposure type            | List:   |
|-------------------|-----------|-----------------------------------|--------------------------|---------|
| Calcium stearate  | 10 mg/m3  | Time Weighted Average (TWA):      |                          | ACGIH   |
| Calcium carbonate | 10 mg/m3  | Time Weighted Average (TWA):      |                          | ACGIH   |
|                   | 5 mg/m3   | PEL:                              | Respirable fraction.     | OSHA Z1 |
|                   | 15 mg/m3  | PEL:                              | Total dust.              | OSHA Z1 |
|                   | 10 mg/m3  | Time Weighted Average (TWA):      |                          | MX OEL  |
|                   | 20 mg/m3  | Short Term Exposure Limit (STEL): |                          | MX OEL  |
| Magnesium oxide   | 10 mg/m3  | Time Weighted Average (TWA):      | Inhalable fraction.      | ACGIH   |
|                   | 15 mg/m3  | PEL:                              | Total particulate.       | OSHA Z1 |
|                   | 10 mg/m3  | Time Weighted Average (TWA):      | Fume. as Mg              | MX OEL  |
| Stearic acid      | 10 mg/m3  | Time Weighted Average (TWA):      | Total dust. as stearates | ACGIH   |
|                   | 10 mg/m3  | Time Weighted Average (TWA):      |                          | ACGIH   |
| Talc              | 2 mg/m3   | Time Weighted Average (TWA):      | Respirable fraction.     | ACGIH   |
|                   | 0.1 mg/m3 | Time Weighted Average (TWA):      | Respirable.              | Z3      |
|                   | 0.3 mg/m3 | Time Weighted Average (TWA):      | Total dust.              | Z3      |

**9. PHYSICAL AND CHEMICAL PROPERTIES**

|                     |                              |                  |                   |
|---------------------|------------------------------|------------------|-------------------|
| Form                | : Solid                      | Evaporation rate | : Not applicable  |
| Appearance          | : pellets, Slabs, sheets     | Specific Gravity | : Not determined  |
| Color               | : RED                        | Bulk density     | : Not established |
| Odour               | : Characteristic rubber odor | Vapour pressure  | : not applicable  |
| Melting point/range | : Not determined             | Vapour density   | : not applicable  |
| Boiling Point:      | : not applicable             | pH               | : not applicable  |
| Water solubility    | : Insoluble                  |                  |                   |

**10. STABILITY AND REACTIVITY**

|                          |  |
|--------------------------|--|
| Stability                | : Stable.  |
| Hazardous Polymerization | : Will not occur.  |
| Conditions to avoid      | : Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat. |
| Incompatible Materials   | : Incompatible with strong acids and oxidizing agents.   |

**EXCEL POLYMERS LLC****MATERIAL SAFETY DATA SHEET****STAN-TONE MB-25462 RED**

Version Number 1.1

Revision Date 11/20/2009

Page 5 of 8

Print Date 2/5/2010

Hazardous decomposition products : Carbon dioxide (CO<sub>2</sub>), carbon monoxide (CO), oxides of nitrogen (NO<sub>x</sub>), other hazardous materials, and smoke are all possible.

**11. TOXICOLOGICAL INFORMATION**

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

| CAS-No.    | Chemical Name     | Effect           | Target Organ                    |
|------------|-------------------|------------------|---------------------------------|
| 471-34-1   | Calcium carbonate | Irritant         | Eyes, Skin.                     |
| 1309-48-4  | Magnesium oxide   | Systemic effects | Eyes, Respiratory system.       |
|            |                   | Irritant         | Eyes, Skin, Respiratory system. |
| 57-11-4    | Stearic acid      | Irritant         | Eyes, Skin.                     |
| 14807-96-6 | Talc              | Systemic effects | Eyes, Respiratory system, Skin. |

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

| CAS-No.   | Chemical Name     | Route       | Value       | Species |
|-----------|-------------------|-------------|-------------|---------|
| 1592-23-0 | Calcium stearate  | Oral LD50   | > 10 gm/kg  | rat     |
| 471-34-1  | Calcium carbonate | Oral LD50   | 6,450 mg/kg | rat     |
| 1309-48-4 | Magnesium oxide   | Oral LD50   | 810 mg/kg   | mouse   |
| 57-11-4   | Stearic acid      | Oral LD50   | 4,600 mg/kg | rat     |
|           |                   | Dermal LD50 | > 5 gm/kg   | rabbit  |

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

| CAS-No.    | Chemical Name | OSHA | IARC | NTP |
|------------|---------------|------|------|-----|
| 14807-96-6 | Talc          | no   | 2B   | no  |

IARC Carcinogen Classifications:

- 1 - The component is carcinogenic to humans.
- 2A - The component is probably carcinogenic to humans.
- 2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

- 1 - The component is known to be a human carcinogen.
- 2 - The component is reasonably anticipated to be a human carcinogen.

**12. ECOLOGICAL INFORMATION**

Persistence and degradability : Not readily biodegradable.

**EXCEL POLYMERS LLC**  
**MATERIAL SAFETY DATA SHEET**



**STAN-TONE MB-25462 RED**

Version Number 1.1  
Revision Date 11/20/2009

Page 6 of 8  
Print Date 2/5/2010

Environmental Toxicity : Chemicals are not readily available as they are bound within the polymer matrix.

Bioaccumulation Potential : Chemicals are not readily available as they are bound within the polymer matrix.

Additional advice : not applicable

**13. DISPOSAL CONSIDERATIONS**

Product : Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.

Contaminated packaging : Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.

**14. TRANSPORT INFORMATION**

U.S. DOT Classification : Refer to specific regulation.

ICAO/IATA (air) : Refer to specific regulation.

IMO / IMDG (maritime) : Refer to specific regulation.

**15. REGULATORY INFORMATION**

US Regulations:

OSHA Status : Classified as hazardous based on components.

TSCA Status : All components of this product are listed on or exempt from the TSCA Inventory.

US. EPA CERCLA Hazardous Substances (40 CFR 302)

not applicable

California Proposition 65 : WARNING! This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

**EXCEL POLYMERS LLC**  
**MATERIAL SAFETY DATA SHEET**



**STAN-TONE MB-25462 RED**

Version Number 1.1  
Revision Date 11/20/2009

Page 7 of 8  
Print Date 2/5/2010

SARA Title III Section 302 Extremely Hazardous Substance

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

Canadian Regulations:

National Pollutant Release Inventory (NPRI)

not applicable

WHMIS Classification : D2A

WHMIS Ingredient Disclosure List

| CAS-No.    |
|------------|
| 1309-48-4  |
| 57-11-4    |
| 14807-96-6 |

DSL : All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

National Inventories:

Australia AICS : Listed

China IECS : Listed

Europe EINECS : Not determined

Japan ENCS : Not determined

Korea KECI : Listed

Philippines PICCS : Listed

**16. OTHER INFORMATION**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The

**EXCEL POLYMERS LLC**  
**MATERIAL SAFETY DATA SHEET**



***STAN-TONE MB-25462 RED***

Version Number 1.1  
Revision Date 11/20/2009

Page 8 of 8  
Print Date 2/5/2010

information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.