



PERFORMANCE ADDITIVES

TECHNICAL DATA SHEET

PRODUCT: BUR-A-LOY XNV-2

DESCRIPTION: Blend of NBR Rubber and PVC Resin
NBR:PVC: Weight % is 70:30
% Bound Nitrile (Wt %) 28.5
Volatile Matter (Wt %) 0.5 Max
Total Ash (Wt %) 1.0 Max
Compound, Bound Nitrile (Wt %) 18

PHYSICAL FORM: Milled Slabs

SPECIFIC GRAVITY: 1.08 (Calculated)

TYPICAL PROPERTIES: Durometer, Shore A, 3 sec..... 60
ASTM D2240
Mooney Viscosity ML(1+4) @212 F 70
ASTM D1646
Tensile Strength, psi (12.4 MPa) 1800
Elongation, % 400
ASTM D412 Method A, 20"/min

STORAGE STABILITY: Typically one year from the date of manufacture when stored under proper conditions in original, sealed container.

Issue Date: 12/14/15 WMS

All property data represents typical values and is not for specification purposes.

* Copies of Hexpol Compounding Test Methods are available upon customer request.

HEXPOL COMPOUNDING MAKES NO WARRANTIES, EXPRESS OR IMPLIED, WITH RESPECT TO THE GOODS OR USE OF THE GOODS OR THE PERFORMANCE OF THE GOODS AND MAKES NO WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE OR MERCHANTABILITY. IN NO EVENT WILL HEXPOL COMPOUNDING BE LIABLE FOR CONSEQUENTIAL, INCIDENTAL, DIRECT OR SPECIAL DAMAGES ARISING, DIRECTLY OR INDIRECTLY, IN RESPECT TO SUCH GOODS OR FAILURE THEREOF, WHETHER BASED ON BREACH OF WARRANTY, NEGLIGENCE, STRICT LIABILITY IN TORT OR OTHERWISE.

HEXPOL Compounding-Performance Additives
14330 Kinsman Rd Burton, OH 44021
USA
Tel: (440) 834-5573
Fax: (440) 299-6569
www.hexpolcompounding.com