



NATROCHEM INC.
P.O. BOX 1205
SAVANNAH, GA 31402
(912) 236-4464 FAX: (912) 236-1919

DATA SHEET NATRO-TAR™ 588

Natro-Tar 588 is Pine Tar and is equivalent to natural Pine Tar in most applications. It is manufactured under closely controlled conditions to insure quality and uniformity. Applications for which it is suitable include cordage and fish nets; as a preservative and fiber lubricant; as a waterproofing medium for tarpaulins, paper, special lubricants, insecticides and paints; in authentic shipbuilding; as a veterinary supply; in tree surgical uses and many others. It is not recommended for use in Pharmaceuticals and Cosmetics, or similar products.

TEST	TEST METHOD	SPECIFICATION
Acid Number	QCL-8.2.4-2-4	65 Max
Viscosity, SFS @ 122°F	QCL-8.2.4-2-5	500 Max
Specific Gravity, @ 80°F	QCL-8.2.4-2-12	1.01 - 1.06
Moisture, %	QCL-8.2.4-2-7	0.6 Max

TYPICAL PROPERTIES

Acid Number	50
Viscosity, SFS @ 122°F	130
Specific Gravity @ 80°F	1.04
Packaging	40# Net Pail or 448# Net Drum

Date of Revision: 12/2/02

The information in this data sheet is derived from the best available sources and is believed to be accurate. However, no guarantee is expressed or implied regarding the accuracy of these data or the use of this product, nor are any statements in this bulletin intended as recommendations to use our products in the infringement of any patents.

OTHER NATROCHEM PRODUCTS

**DLC® s - Galex® - Rosin Oils - Rosin Pitches - Tarenes™
Natro-Flex™ - Tar-Cel® - Natro-Cel®**