



## Product Literature

ISO 9001:2008 REGISTERED

---

**POLYCIZER® TOTM**  
**Trioctyl Trimellitate**  
**CAS# 3319-31-1**

Polycizer TOTM is a monomeric polyester plasticizer that is widely used as a stable, low volatility plasticizer in rubber and plastic compounds. It is found to be particularly useful in CPE compounds, where it has good compatibility, and offers good low-temperature properties, combined with good heat aging characteristics.

### **TYPICAL PROPERTIES**

Ester, %	99.95
Acidity, % as Trimellitic Acid	0.005
Color, Pt/Co	50
Specific Gravity @ 20/20°C	0.989
Refractive Index @ 25°C/77°F	1.483
Viscosity @ 25°C/77°F, cSt.	196
Pour Point °C/°F	-46/-50
Flash Point °C/°F	263/490

Polycizer® is a Registered Trademark of Harwick Standard Distribution Corporation

10/9/98 – Revised 6/4/13

---

HARWICK STANDARD MAKES NO WARRANTIES, EXPRESS OR IMPLIED, WITH RESPECT TO THE GOODS OR USES OF THE GOODS OR PERFORMANCE OF THE GOODS AND MAKES NO WARRANTIES OF THE FITNESS FOR PARTICULAR PURPOSE OR MERCHANTABILITY. BUYER ACKNOWLEDGES THAT HARWICK STANDARD WILL NOT BE LIABLE FOR CONSEQUENTIAL, INCIDENTAL, DIRECT OR SPECIAL DAMAGES ARISING, DIRECTLY OR INDIRECTLY, IN RESPECT TO SUCH GOODS OR THE USE OR FAILURE THEREOF, WHETHER BASED ON BREACH OF WARRANTY, NEGLIGENCE, STRICT LIABILITY IN TORT OR OTHERWISE.

**HARWICK STANDARD DISTRIBUTION CORPORATION**  
60 S. SEIBERLING ST. • P.O. BOX 9360 • AKRON, OH 44305-0360 • U.S.A.  
PHONE: (330) 798-9300 • FAX: (330) 798-0214  
[WWW.HARWICKSTANDARD.COM](http://WWW.HARWICKSTANDARD.COM)