



HARWICK

S T A N D A R D

ISO 9001-2015 REGISTERED

Technical Data Sheet

Stan-Mix™ HMT S/50

Stan-Mix HMT S/50 is a 50% Hexamethylenetetramine Dispersed in Styrene-butadiene Rubber.

TYPICAL PROPERTIES

Activity Level of Main Ingredient:	50%
Physical Form:	Milled Slab
Specific Gravity:	1.18
Storage Stability:	Store in a constant temperature range of 50°F to 70°F, keeping lid sealed tightly, for best stability.

10/26/2023

HARWICK STANDARD MAKES NO WARRANTIES, EXPRESS OR IMPLIED, WITH RESPECT TO THE GOODS OR USES OF THE GOODS OR PERFORMANCE OF THE GOODS AND MAKES NO WARRANTIES OF THE FITNESS FOR PARTICULAR PURPOSE OR MERCHANTABILITY. BUYER ACKNOWLEDGES THAT HARWICK STANDARD WILL NOT BE LIABLE FOR CONSEQUENTIAL, INCIDENTAL, DIRECT, OR SPECIAL DAMAGES ARISING, DIRECTLY, OR INDIRECTLY, IN RESPECT TO SUCH GOODS OR THE USE OR FAILURE THEREOF, WHETHER BASED ON BREACH OF WARRANTY, NEGLIGENCE, STRICT LIABILITY IN TORT OR OTHERWISE.

HARWICK STANDARD DISTRIBUTION CORPORATION

60 S. SEIBERLING ST. • P.O. Box 9360 • AKRON, OH 44305-0360 • U.S.A.

PHONE: (330) 798-9300 • www.harwick.com