



ZINC OXIDE GRADE AZO66

Description & Uses

Grade AZO66 is an extremely pure French Process, statistically controlled zinc oxide produced from zinc metal. AZO66 provides superior color and is highly efficient in light colored or white goods. This grade is used in the zinc chemical, oil additive, ceramic, paint/coating industries and in those applications where high purity is critical. Grade AZO66 is available with surface treatment (AZO66T) and in a pelleted form (AZO66P).

Typical Technical Values*

Chemical Analysis (%)	Range	Nominal	Method
ZnO (Zinc Oxide)	≥ 99.7%	99.8%	USZ
Pb (Lead)	≤ 0.005%	0.003%	D4075
Cd (Cadmium)	≤ 0.003%	0.001%	D4075
Cu (Copper)	≤ 0.002%	nil	D4075
Fe (Iron)	≤ 0.002%	nil	D4075

Physical Properties

Surface Area (m ² /g)	4.0-6.0	5.0	D4315
Fineness passing 325 mesh (%)	≥99.9	99.98	D4315
Heat Loss/Moisture (%)	< 0.2%	0.1%	D280
Specific Gravity	N/A	5.6	USZ
Apparent Density (Powder)	20-40	30	USZ
Apparent Density (Pellets)	50-85	65	USZ

Standard packaging in 50 pound net weight bags on 48X40 wood pallets. 2,500 pounds net weight.

**U.S. Zinc can produce Zinc Oxide to meet individual customer specifications superseding the above. Please contact customer service for additional information.*

Revised 04/24/2015

U. S. ZINC

2727 Allen Parkway, Suite 800 Houston TX 77019 USA.

Phone (001) 713-926-1705, Fax (001) 713-924-4828

Info@USZinc.com WWW.USZinc.com